

# **OPTICO Standard Pigtail Datasheet**

Ideal for CATV, FTTH/FTTX, telecommunication networks, premise installations, data processing networks, LAN/WAN network, and more.




## Description

OPTICO offers a full line of simplex or Bundle Fiber Pigtails. Fiber pigtail is an important component of fiber network. It is at the end of the SC/LC/ST/FC/E2000 / MTP/MPO/MTRJ optical fiber connector, the other end for termination by fusion or mechanical splicing fiber optic cable. A typical 900µm tight buffer layer is adopted by default for easy fusion. OPTICO's use of high quality raw materials, rigorous production processes and quality control has made it a trusted brand for 15 years.

## Features

- Tested on optical performance insertion loss and return Loss.
- 0.9mm cable for high density splicing applications.
- Tight buffer for easy fusion or mechanical splicing
- LC, ST, SC, FC and LSH are available.
- UPC and APC polish type
- PVC jacket as default, OFNP and LSZH are optional.
- High reliability and stability
- High quality CCTC ceramic ferrules

#### Cable structure







# Shenzhen OPTICO Communication Co., Ltd.

# • Technical Specifications

Item	Parameter
Fiber Count	Simplex
Fiber Mode	Singlemode:OS2 Multimode:OM1/OM2/OM3/OM4
Connector Type	SC/LC/ST/FC/E2000/MTRJ/LSH
Polish Type	APC/UPC
Jacket Color	SM:Yellow/white OM1/2:Orange OM3/4: Aqua
Jacket Ratings	PVC/LSZH
Outer Cable Diameter(mm)	0.9/2.0
Minimum Bending Radius	5D/10D(Static/Dynamic)

Optical Testing	Parameter
Insertion Loss(dB)	≤0.25
Return Loss(dB)	SMF: UPC≥50, APC≥60 (LC/SC/ST/FC) UPC≥55, APC≥75 (LSH) MMF: UPC≥30 (LC/SC/ST/FC/LSH)
Wavelength(nm)	SMF: 1310/1550; MMF: 850/1300
Attenuation(dB/Km)	SMF: ≤0.36 at 1310nm, ≤0.22 at 1550nm MMF: ≤3.0 at 850nm, ≤1.0 at 1300nm
Operating Temperature(°C)	-40~85
Storage Temperature(°C)	-40~85

# • Tips:

In order to make the customers know us more, please visit our VR factory, it is just like you were really standing in our factory.

OPTICO Fiber Assemblies Production Line VR: https://www.linked-reality.com/company/15555/en





